

Product	State	Grade	Applications	Packing
Flame Retardant for coating/resin/polymer	Powder	GY-FR-B21 GY-FR-B24 GY-FR-OP series	 Excellent flame retardant effect , provide added-value for products Good thermal cracking temperature Excellent thermal stability Good compatibility and dispersion 	25KG/bag
Anti-UV, Anti- yellowing agent for coating/resin/polymer	Powder Liquid	GOYENCHEMUV-700 GGK-690	 Preventing yellowing and aging caused by external factors, weather, light Long-term barrier Good anti-yellowing, enhance the weather resistance of coating, resin in various environments, temperatures or processing Low volatility and good heat stability 	25KG/bag 20KG or 200K/drum
Anti-static agent for coating/resin/polymer	Powder Liquid	GYC-AT-300 GYC-AT-786	 Good antistatic property Effectively reduce surface resistance of products Lower and more economical dosages Uniformity of coating thickness 	20KG/BAG 190 /200 KG/drum
Matting agent for coating/resin/polymer	Powder	GY-MT412 GY-MT32	 Excellent matting effect Decrease the gloss of resin, will not occur the produce glare phenomenon Good processing ability and good dispersion Give the product a low-key luxurious texture 	10KG/bag 25KG/bag
Antifoaming agent for coating/resin/polymer	Liquid	GY-LA56/LA-21 (water base) GY-LA (oil base)	 Give the product excellent antifoaming ability and foam breaking. Prevent crater phenomenon of coating due to the dried foam It has excellent water dilution and is not easy to stratify. Excellent compatibility with various coatings and resins 	25KG or 50KG/drum



Product	State	Grade	Applications	Packing
Dispersing agent for	Liquid	GY-LW (water base)	It can make the surface of the product	180KG/drum
coating/resin/polymer		GY-LO (oil base)	with smooth and heat stability .	
			 Change plasticity and even coloration. 	
			 Promote dispersing ability and lubricant 	
			for various pigments and resins	
Anti-scratch agent for	Liquid	GOYENCHEM-14	Improve the abrasion resistance of	25KG/drum
coating/resin/polymer		(oil base)	resin and oil system products and give	
		GGK-1440/GGK-	scratch resistance for products	
		1460(water base)	 Improve the strength of resin, 	
			coating , film	
			 Good compatibility for various resin, 	
			coating	
Antibiotic agent for	Liquid	GY-ANTIBIOTIC-100	Avoid moldiness caused by humid and	20KG/drum
coating/resin/polymer	'		rainy weather	,
, , , , , , , , , , , , , , , , , , ,			Provide good and long-term	
			antibacterial properties	
			Good compatibility	
Antioxidant for	Solid or	GOYENCHEM-AO1010	High effect antioxidant	20KG/bag
coating/resin/polymer	powder	GOYENCHEM-AO1076	Effectively inhibit oxidative	
		GOYENCHEM-AO168	degradation of polymers during	
		GOYENCHEM-AO series	processing	
			Good compatibility	
			 Avoid deterioration during product 	
			processing	
			Can be used with other aids	
Titanium dioxide for	Powder	GR SERIES	Weather resistance	25KG/bag
coating/resin/polymer			Good coloring ability and whiteness	
			Excellent dispersion	
Wear-resistant agent for	Powder	GGK-1402	Provide good wear resistance of the	25KG/bag
coating/resin/polymer			coating and very fine powder,	
			excellent dispersion	
			Improve the mechanical properties of	
			the film	



Product	State	Grade	Applications	Packing
Rheology Control	Liquid	GY-VE SERIES	Improve anti-sagging effect of resin	25KG or
Additive for			Give paint products fluidity and	200KG/drum
coating/resin/polymer			leveling ability	
			 Coating film anti-splash properties of 	
			coating	
			Effectively increase product added	
			value	
color brightener for	Pellet	GY-HL series	Raise gloss	25KG/bag
coating/resin/polymer			 Enhance brightness of surface, 	
			granting high added-value of product	
			Can be used for colored and colorless	
			products to improve product gloss	
Impact modifier for	Powder	GY-EA-100P	 Improve resin/ink/coating adhesion 	20KG/bag
coating/resin/polymer			Good fluidity and low melting point	
			Easy processing	
Anti-fish eyes &	Liquid	GOYENCHEM-144	 Prevent fish eyes and volcanic vents 	25KG/drum
volcanic vents agent			on the top of coating	
			 To avoid poor performing caused by 	
			mix unevenly or bad dispersion	
			Sustain the smoothness of shaped	
			products	
			Enhance the adherence of topcoat	
			With excellent compatibility with	
			various surface treatment, coating	
			and resin	
Anti-skinning Agent	Liquid	GY-A	 Excellent anti-skinning, does not 	25KG/drum
for			affect the coating drying rate	
coating/resin/polymer			Compatible with a variety of paints	
			and coatings, for use in preventing	
			oxidative polymerization drying paint	
			Prevent the surface crust caused by	
			storage or transport process	
			Won't let the coating fade or discolor	



Product	State	Grade	Applications	Packing
Water base emulsion	Liquid	GOYENCHEM-WE03	Base materials for various water-	200KG/drum
resin		GOYENCHEM-WE18	based fire retardant coatings,	
			architectural coatings, waterborne	
			coatings, interior and exterior wall	
			coatings	
			High brush stability	
			High thermal stability	
			Give color retention	
Anti-cavity anti-	Liquid	GOYENCHEM-143	Adding to the coating can remove	25KG/drum
cratering agent for			defects such as pits and shrinkage	
coating/ resin/			holes caused by grease and release	
polymer			agent contamination	
			 Good compatibility for various resin 	
			and coating	

During 40 years experiences in fine chemical field, GYC Group has made a barrier to competitors and imitators because of our incomparable technology. Nowadays, GYC Group has exported our products over than 60 countries.

We provide comprehensive products and total solutions for customers, if you have other requirement, please browse our website:

https://www.gyc-speciality-chemicals.com or

www.goyenchemical.com





GO YEN CHEMICAL INDUSTRIAL CO., LTD. (GYC GROUP)

Head Office: 5F , No.232, Kuang-Hwa 1St Rd. , Lin-Ya District Kaohsiung. Taiwan (Post Code: 80253) TEL:886-7-2272766 / FAX:886-7-2272768

Factory I: No.39 Shing Yeh St. Lin Hai Industrial Area Kaohsiung, Taiwan Factory II: No.10 Shing Yeh St. Lin Hai Industrial Area Kaohsiung, Taiwan

Overseas Factory III: 1054-A, Jalan Aman 5, Kawasan Industri Taman Makmur, Lunas, Kedah, Malaysia

www.goyenchemical.com